GROUP 600 ACCESORIES MOD.

MOD. 611A/80





TECHNICAL DATA SHEET

WATER Series

COUPLING FOR PVC/PE/HDPE PIPES







www.davincivalves.com

WATER series



RESTRAINED COUPLING FOR PVC/PE/HDPE/UPVC

Ref.611A / PN 16

APPLICATION:

Water, HVAC installations, irrigation, industry, others

WORKING CONDITIONS:

Working Temperature:

- 10 °C + 120 °C. for EPDM
- 10 °C + 82 °C. for NBR




Size DN300 to DN1200, Connection for HDPE Angular deflection +-4° working pressure PN10/PN16 Powder Epoxy Cured coating 250 Mic



Comply with EN545/12842 Coating Standard EN30677 Pressure Test: EN 12266-1. Flange EN1092-2 PN10/PN16 WRAS approval under request

Sr.No.	Name	Material
1	End ring	Ductile Iron
2	Gripper	Galvanized cast iron
3	Gripper Bolt	Carbon steel
4	Gasket	EPDM
5	Ring Bolt	Carbon steel
6	Body	Ductile Iron



DE	L	D	M*L	К	M16*N
355	170	510	M16*300*6	473	M16*6
400	180	556	M16*320*8	518	M16*8
500	180	658	M16*320*8	620	M16*8
630	200	790	M16*360*10	750	M16*10
710	200	870	M16*360*12	830	M16*12
800	220	965	M16*400*12	922	M16*12
900	220	1070	M16*400*14	1025	M16*14
1000	220	1172	M16*400*14	1128	M16*14
1200	240	1380	M16*430*16	1330	M16*16

All the components can be substituted with equivalent or higher-class materials.

DAVINCI VALVES LTD, is constantly looking at all ways of improving our products and services related to the water, fire and industry sector and therefore we reserve the right to change, without prior notice, any of the data contained here. Please contact our Technical Sales Department for detailed advice.

© 2018 DAVINCI VALVES LTD.

"For profesionals who wants more"

