





# TECHNICAL DATA SHEET

### **INDUSTRY Series**

Y TYPE SPRING CHECK VALVE THREAD END







www.davincivalves.com

## INDUSTRY



#### Y TYPE SPRING CHECK VALVE THREAD END

#### Ref.432A.137

#### **APPLICATION:**

Suitable for use in Industry, heat /cooling systems and others.

#### **GENERAL CHARACTERISTICS:**

Range from 1/4" up to 2" Installation in any position. High mechanical resistance Total tightness. Low cost installation and maintenance.


#### **WORKING CONDITIONS:**


Maximum Working Pressure: 1000psi /PN64. Max.Working Temperature: -20 °C / +190 °C Suitable Media: Water, Oil, Gas, others. Consult Factory for other applications

#### STANDARDS:

ASME B1.20.1 (NPT) / DIN 2999 & BS 21 100% sealing according to: ISO 5208 Rate A. Manufacture acc. to the requirements of the EU directive 2014/68/EU Equipment under pressure: Cat. III mod. H Inspection Testing API598 EN12266

ITEM	PART	MATERIAL
1	BODY	CF8M
2	NUT	CF8
3	DISC SEAT	PTFE
4	DISC	CF8M
5	SPRING	SS04
6	GASKET	PTFE
7	BONNET	CF8M





SIZE	А	Н	L	S
1/4"	15	58	65	26
3/8"	15	58	65	26
1/2"	15	58	65	26
3/4"	20	68	79	33
1"	25	88	89	41
1.1/4"	32	100	105	59
1.1/2"	40	108	120	56
2"	50	130	140	69

All the components can be substituted with equivalent or higher-class materials.

"For profesionals who wants more"

