GROUP 600 ACCESORIES

MOD. 632/84





TECHNICAL DATA SHEET

WATER Series

DUCTILE IRON CLAMP







www.davincivalves.com

WATER series



DUCTILE IRON REPAIR CLAMP

Ref.632A / PN 10-16

APPLICATION:

Water, HVAC installations, irrigation, industry, others

WORKING CONDITIONS:

Working Temperature: - 10 °C - + 120 °C. for EPDM - 10 °C - + 82 °C. for NBR



GENERAL CHARACTERISTICS:


Size DN50 to DN300, working pressure PN10/PN16 Body pn16


STANDARDS:

Comply with EN545

Materials Specification

Sr.No.	Name	Material			
1	Body	Ductile Iron			
2	Body	Ductile Iron			
3	Bridge Plate	SS304			
4	Gasket	EPDM/NBR			
5,6&7	Tie rods	CS/SS			





Dimensions(mm)

DN	50	65	80	100	125	150	175	200	200	225	250	300
Range	66-75	75-84	93-103	115-125	141-153	166-181	200-210	217-226	231-243	243-267	269-294	323-349
х	150	159	184	211	239	267	296	313	328	362	395	450
Y(max)	110	119	145	167	182	217	238	269	281	307	322	387
Z	200	200	200	200	200	200	200	200	200	200	250	300
Outlet threaded	3/4"	3/4"	3/4"	1/2"- 1"	1/2"- 1"	1/2"- 1"	1/2"- 1"	1/2"- 1"	1/2"- 1"	1/2"- 1"	1/2"- 1"	1/2"- 1"

All the components can be substituted with equivalent or higher-class materials.

DAVINCI VALVES LTD, is constantly looking at all ways of improving our products and services related to the water, fire and industry sector and therefore we reserve the right to change, without prior notice, any of the data contained here. Please contact our Technical Sales Department for detailed advice.

© 2018 DAVINCI VALVES LTD.

"For profesionals who wants more"

