





TECHNICAL DATA SHEET

INDUSTRY Series

2-PC BALL VALVE DIN F4/F5 WITH DIRECT MOUNTING PAD FLAN GED END PN16-40 WITH FIRE SAFE DEVICE







www.davincivalves.com

INDUSTRY



3 PIECE BALL VALVE SS316 1000WOG THREAD END

Ref.742A

APPLICATION:

Potable water distribution and pumping, sewage, irrigation

WORKING CONDITIONS:

Pressure Ratings: 1000 PSI

Working Temperature: --30°C +250°C


Suitable Media: Water Oil Gas


End connection: Thread end GAS/NPT Consult Factory for other applications


GENERAL CHARACTERISTICS:

Size Range: 1/4" ~4" Full bore.

100% Tightness in both ways. Block device








STANDARDS:

Pressure Test: API 598, EN 12266



ITEM	DESIGNATION	QTY	MATERIAL
1	Hand Sleeve	1	PVC
2	Handle	1	304
3	Gland Nut	1	304/316
4	Stem Nut	1	304
5	Stem Washer	1	304
6	Spring Packing	1	PTFE
7	Thrust Washer	1	PTFE
8	End Cap	1	CF8/CF8M
9	Bolt	4(6)	304
10	Nut	4(6)	304
11	Spring Washer	4(6)	304
12	Body	1	CF8/CF8M
13	Ball Seat	2	RPTFE
14	Ball	1	CF8/CF8M
15	Stem	1	304/316
16	Locking Device	1	304

SIZE\ITEM	D	L	Н	W
1/4"	11	50	48	48
3/8"	12	50	48	48
1/2"	15	60	52	52
3/4"	20	70	61	61
1"	25	80	65	65
1.1/4"	32	93	79	79
1.1/2"	38	100	83	83
2"	50	125	97	97
2.1/2"	64	158	135	135
3"	76	179	144	144
4"	94	223	172	172

All the components can be substituted with equivalent or higher-class materials.

DAVINCI VALVES LTD, is constantly looking at all ways of improving our products and services related to the water, fire and industry sector and therefore we reserve the right to change, without prior notice, any of the data contained here. Please contact our Technical Sales Department for detailed advice.

© 2018 DAVINCI VALVES LTD.

"For profesionals who want more"

